

ATEM SDI



ATEM SDI is fast to set up and easy to use. It includes 4 standards converted SDI inputs, USB webcam, 2 SDI outputs, Fairlight audio mixer with EQ and dynamics, DVE for picture in picture, transition effects, green screen chroma key, 20 stills media pool for titles and free ATEM Software Control.

£275

Connections

Total Video Inputs

4

Total Outputs

3

Total Aux Outputs

2

Total Audio Inputs

2 x 3.5mm stereo mini jack.

Total Audio Outputs

None, embedded audio only.

Timecode Connection

None

SDI Video Inputs

4 x 3G-SDI, 10-bit HD switchable.

2 channel embedded audio.

Video Input Re-Sync

On all 4 SDI inputs.

Frame Rate and Format Converters

On all 4 SDI inputs.

SDI Program Outputs


2

Ethernet

Ethernet supports 10/100/1000 BaseT software control, software updates and direct or network panel connection.

Computer Interface

1 x USB Type-C 2.0 for webcam out, software control, software updates and panel connection.



Standards

HD Video Input Standards

720p50, 720p59.94, 720p60
 1080p23.98, 1080p24, 1080p25,
 1080p29.97, 1080p30, 1080p50,
 1080p59.94, 1080p60
 1080i50, 1080i59.94, 1080i60

HD Video Output Standards

1080p23.98, 1080p24, 1080p25,
 1080p29.97, 1080p30, 1080p50,
 1080p59.94, 1080p60

Video Streaming Standards

1080p23.98, 1080p24, 1080p25,
 1080p29.97, 1080p30, 1080p50,
 1080p59.94, 1080p60

Ultra HD Video Standards

None

Video Sampling

4:2:2 YUV

Color Precision

10-bit

Color Space

Rec 709

Colorspace Conversion

Hardware based real time.

Product Specifics

Upstream Keyers

1

Downstream Keyers

1

Advanced Chroma Keyers

1

Linear/Luma Keyers

2

Transition Keyer

DVE only.

Total Number of Layers

5

Pattern Generators

1

Color Generators

2

DVE With Borders and Drop Shadow

1

Interface

Minimum monitor resolution of 1366 x 768.

Audio

Audio Mixer

6 input x 2 channel mixer.
Selectable On/Off/Audio-Follow-Video per channel plus separate gain control per channel.
Level and Peak metering. Plus new Fairlight audio enhancements: Compressor, Gate, Limiter, 6 bands of parametric EQ. Master gain control.

Analog Input

Unbalanced stereo

Analog Input Delay

Up to 8 frames

Input Impedance

1.8k

Max Input Level

+6dBV

Mic Plug In Power

Available on both 3.5mm mini jack connections.

Media Player

Media Players

1

Media Pool Still Image Capacity

20 with fill and key.

Channels

Fill and key for each Media Player.

Media Pool Still Image Format

PNG, TGA, BMP, GIF, JPEG and TIFF.

Control

Control Panel

Built in control panel. Supports optional hardware panel.
ATEM Software Control Panel for Mac and Windows included for free.

Control Panel Compatibility

Compatible with ATEM Micro Panel, ATEM 1 M/E Advanced Panels, ATEM 2 M/E Advanced Panels, ATEM 4 M/E Advanced Panels plus ATEM Camera Control Panel and ATEM Micro Camera Panel. ATEM can also be configured using Blackmagic Videohub Hardware Panel Setup utility to route sources to destinations using Videohub Smart Control Pro and Videohub Master Control Pro.

Control Panel Connection

Ethernet supports 10/100 BaseT. Allows direct connection between panel and chassis, or via network. Also used for updating the software. ATEM SDI supports direct USB-C connection.

Software

Control Panel Included

ATEM Software Control panel included free for Mac and Windows.

Software Updates

Using USB or Ethernet connection directly connected to Mac or Windows computers. Includes ATEM Setup Utility

Configuration

Most switcher configurations are set in ATEM Software Control. To set an ATEM switcher IP address, use the ATEM Setup Utility with a direct USB connection to the switcher.

Operating Systems



Mac 14.0 Sonoma,
Mac 15.0 Sequoia or later.



Windows 10 and 11.

Power Requirements

Power Supply

1 x External 12V power supply.

Power Usage

18W

Physical Specifications



Environmental Specifications

Operating Temperature 5° C to 40° C (41° - 104° F)	Storage Temperature -10° to 60° C (14° to 140° F)	Relative Humidity 0% to 90% non-condensing
--	---	--

What's Included

ATEM SDI
External 12V DC power supply with international socket adapters

Warranty

1 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2026, all rights reserved.
All trademarks are property of their respective owners. MSRP excludes VAT and local shipping costs.
This website uses remarketing services to advertise on third party websites to previous visitors to our site.
You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller