

ATEM SDI Extreme ISO



This model includes all the features of ATEM SDI Pro ISO model but has 8 SDI inputs and 4 SDI outputs. It can record 9 separate H.264 video streams in real time, allowing capture of all 8 clean feed inputs as well as the program video. A DaVinci Resolve project file is also saved.

\$1,715

Connections

Total Video Inputs

8

Total Outputs

6

Total Aux Outputs

4

Total Audio Inputs

2 x 3.5mm stereo mini jack.

Total Audio Outputs

1 x 3.5mm stereo mini jack.

Timecode Connection

None

SDI Video Inputs

8 x 3G-SDI, 10-bit HD switchable.
2 channel embedded audio.

Video Input Re-Sync

On all 8 SDI inputs.

Frame Rate and Format Converters

On all 8 SDI inputs.

SDI Program Outputs


4

Ethernet

Ethernet supports 10/100/1000 BaseT for live streaming, software control, software updates and direct or network panel connection.

Computer Interface

2 x USB Type-C 3.1 Gen 1 for external drive recording, webcam out, software control, software updates and panel connection.



Standards

HD Video Input Standards

720p50, 720p59.94, 720p60
1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p50,
1080p59.94, 1080p60
1080i50, 1080i59.94, 1080i60

HD Video Output Standards

1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p50,
1080p59.94, 1080p60

Video Streaming Standards

1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p50,
1080p59.94, 1080p60

Ultra HD Video Standards

None

Video Sampling

4:2:2 YUV

Color Precision

10-bit

Color Space

Rec 709

Colorspace Conversion

Hardware based real time.

Product Specifics

Upstream Keyers

4

Downstream Keyers

2

Advanced Chroma Keyers

Up to 4

Linear/Luma Keyers

Up to 4

Transition Keyer

DVE only.

Total Number of Layers

9

Pattern Generators

5

Color Generators

2

DVE With Borders and Drop Shadow

2

Interface

Minimum monitor resolution of 1366 x 768.

Audio

Audio Mixer

11 input x 2 channel mixer.
Selectable On/Off/Audio-Follow-Video per channel plus separate gain control per channel.
Level and Peak metering. Plus new Fairlight audio enhancements: Compressor, Gate, Limiter, 6 bands of parametric EQ. Master gain control.

Analog Input

Unbalanced stereo

Analog Input Delay

Up to 8 frames

Input Impedance

1.8k

Max Input Level

+6dBV

Mic Plug In Power

Available on both 3.5mm mini jack connections.

USB Audio Output

Supports digital audio output over USB-C.
Fully integrates with Fairlight Live.
[Learn More](#)

Streaming

Direct Streaming

Supports direct live streaming using Real Time Messaging Protocol (RTMP) and Secure Reliable Transport (SRT) over ethernet or a shared internet connection over USB-C.

Blackmagic Cloud Stream Router

Supports streaming to Stream Router application in Blackmagic Cloud.

Recording

Direct Recording Video and Audio

USB-C 3.1 Gen 1 expansion port can record directly to external media.

Video Recording

8 x SDI ISO inputs as H.264 .mp4 files at up to 70Mb/s quality at the ATTEM video standard with AAC audio.
1 x Program out as H.264 .mp4 file at the Streaming quality setting and at the ATTEM video standard with AAC audio.

Audio Recording

10 x 2 channel audio inputs recorded as separate 24-bit 48KHz .wav files. Including 2 x analog 2 channel audio inputs and 8 x SDI 2 channel embedded audio inputs.

Switching

Program switching recorded as a DaVinci Resolve project .drp file.

Media Format

Supports media formatted ExFAT (Windows/Mac) or HFS+ (Mac) file system.

Cloud Synchronization



Blackmagic Cloud

[Learn More](#)

Multi View Monitoring

Multi View Monitoring

Configurable to 16, 13, 10, 7 or 4 up views including Program, Preview, 8 SDI inputs, SuperSource, Clean Feed, Media Player, Streaming Status, Recording Status and Audio Meters.

Multi View Video Standard

HD

Media Player

Media Players

2

Media Pool Still Image Capacity

20 with fill and key.

Channels

Fill and key for each Media Player.

Media Pool Still Image Format

PNG, TGA, BMP, GIF, JPEG and TIFF.

Control

Control Panel

Built in control panel. Supports optional hardware panel. ATEM Software Control Panel for Mac and Windows included for free.

Control Panel Compatibility

Compatible with ATEM Micro Panel, ATEM 1 M/E Advanced Panels, ATEM 2 M/E Advanced Panels, ATEM 4 M/E Advanced Panels plus ATEM Camera Control Panel and ATEM Micro Camera Panel. ATEM can also be configured using Blackmagic Videohub Hardware Panel Setup utility to route sources to destinations using Videohub Smart Control Pro and Videohub Master Control Pro.

Control Panel Connection

Ethernet supports 10/100/1000 BaseT. Ethernet used for direct connection between panel and chassis or via network. ATEM SDI Extreme ISO also supports direct USB-C connection. Ethernet or USB-C used for updating the software.

Software

Control Panel Included

ATEM Software Control panel included free for Mac and Windows.

Software Updates

Using USB or Ethernet connection directly connected to Mac or Windows computers. Includes ATEM Setup Utility

Configuration

Most switcher configurations are set in ATEM Software Control. To set an ATEM switcher IP address, use the ATEM Setup Utility with a direct USB connection to the switcher.

Operating Systems



Mac 14.0 Sonoma,
Mac 15.0 Sequoia or later.



Windows 10 and 11.

Power Requirements

Power Supply

1 x External 12V power supply.

Power Usage

36W

Physical Specifications



Environmental Specifications

Operating Temperature

5° C to 40° C (41° - 104° F)

Storage Temperature

-10° to 60° C (14° to 140° F)

Relative Humidity

0% to 90% non-condensing

What's Included

ATEM SDI Extreme ISO
External 12V DC power supply with international socket adapters

Warranty

1 Year Limited Manufacturer's Warranty.

Blackmagic Design Authorized Reseller